



RYETEC ZOCON GREENSEEDER

MAIZE INTO ROW GRASSSEEDER

The greenseeder has been designed to undersow grass into maize post establishment. Providing great soil stabilisation as efficiently as possible.

Standard Specification

- » A high frame with a large ground clearance of 850mm to work in tall crops.
- » 5-stage adjustment of the spring pressure on teeth elements.
- » A unique headland positioner: elements lift high above the crop, allowing turning without damaging the maize plants.
- » 10 mm double tines.
- » Completely galvanized.
- » Isobus and various options available.
- » Available in widths from 4.5M to 9.5M.



Various widths available



10mm following tines with five different settings



Well established crop at the point of harvest

For more information contact Ryetec Industrial Equipment Limited
 Mill House, A64 East Knapton, Malton, North Yorkshire YO17 8JA
 T: 01944 728 186 | www.ryetec.co.uk | [f](https://www.facebook.com/ryetec) /ryetec





RYETEC ZOCON PRECISION TINED WEEDER

PRECISION TINE WEEDER SUITABLE FOR MOST CROPS AND GROWTH STAGES

A mechanical tined weeder aimed at replacing the need for chemical-synthetic pesticides in the most efficient and cost effective way.

The precision tined weeder has several unique features that make it a great machine, meaning it can be used right away from the drilling stage onwards in a wide range of crops. A robust, durable machine with a wide range of fine adjustment on the tines allows it to work as a very gentle harrow or more aggressively when required.

Standard Specification

- » Suitable for weeding from a very early stage in a wide variety of crops.
- » Working widths of 3-15M.
- » 7 rows of 7mm tines with a 2.2cm spacing.
- » East hydraulic tine pressure adjustment (0.1KG-5kg) with mechanical tine angle adjustment.
- » Tine pressure equal at every working height
- » Easy depth/aggressiveness adjustment with rear swivelling guide wheels.

Options:

- » Seeders available 150L, 300L or 450L.
- » Tine deactivation per tine.
- » Front linkage mounted machine.
- » Electronic control with display.



Hydraulic tine pressure adjustment across the full machine



Rear swivelling guide wheels for excellent contour following

For more information contact Ryetec Industrial Equipment Limited
 Mill House, A64 East Knapton, Malton, North Yorkshire YO17 8JA
 T: 01944 728 186 | www.ryetec.co.uk | [f](https://www.facebook.com/ryetec) /ryetec

