

Professional Out Front Flail Mowers

Features

- Models available to suit most specialist out front mowing tractors (see spec below).
- Fully floating to follow ground contours.
- Standard half Y grass flail, Optional fine finish HD Cast "DELTA" paddle flail.
- Strong front flap stops flying object but allows long grass into the mower to be cut easily in one pass.
- Removable mulching bar fitted
- Heavy duty gearbox, oil immersed cross shaft and bearings, for cool running and long service life.
- Triple V belt drive to flail rotor.
- Overrun clutch to protect drive line.
- Easy cutting height control with rear roller and front castor wheels.
- Remote greasing of rotor bearings.



- Solid tyre castor wheels (with inboard option)
- Full width rear roller
- Even spread of cut grass
- Belt guard side protection
- Optional scarifying blades

With standard "Y" flails and side mounted castors, cutting very long grass effectively in one pass is no problem.

Inboard caster kits are also available as an option.

Easy adjustment of cutting height on both the roller and caster wheels.



PF1600HD is the model in all the images

Professional Out Front Flail Mowers

Flails



Y-Flail on PF1600

Heavy Duty Y Flail
on PF1600HD

Optional Delta
Flail gives finer
finish



HD vs Standard Machine

- HD has thicker chassis frame and therefore is a heavier machine.
- HD can deal with larger amounts of grass due to its larger diameter flail shaft and larger flail hood.
- Standard machine can be fitted with scarifying blades but HD cant.
- HD machine has larger front caster wheels.
- Larger Y flails 5mm thick are fitted on HD model as shown in images above, standard flails are 4mm thick.

Specifications

Model	Tractor	Width of cut mm	Weight kg	No. of Y flails (paired)	No. of paddle flails/scarifying blades
PF1600	John Deere F1435/45—F1564—F1550—F1570	1600	227	100	50
PF1600HD	John Deere F1445—F1550—F1570/75—F1580/85	1600	250	100	50
PF1800HD	John Deere F1570/75—F1580/85	1800	280	116	58